

TRAILBLAZER™

UTV V-PLOW



Blaze new trails with your UTV. Whether you plow snow for a living, or just want to get more out of your utility vehicle, the TRAILBLAZER™ UTV V-plow delivers the *professional-grade* snow plow features you expect from Fisher Engineering. The TRAILBLAZER UTV V-plow easily adjusts to pass through gates and clear 5' sidewalks. Designed to fit a wide variety of models, the TRAILBLAZER UTV V-plow will turn your UTV into a winter workhorse.

The Legacy Rolls On



TRAILBLAZER™

BLAZE A TRAIL

6' V-PLOW BLADE

- 6' powder-coated steel, flared moldboard
- Standard 5" steel cutting edge for a clean scrape and extended wear
- 5' wide or less when fully angled, in scoop or in V mode to fit most sidewalks and maneuver through gates

STURDY V-PLOW CONSTRUCTION

- Constructed with high-strength, low alloy steel components that are both stronger and lighter than traditional steel
- Reinforced with six vertical ribs and our proven T-frame design so your UTV can work hard without having to carry extra weight



DOUBLE-ACTING CYLINDERS

Standard double-acting 1" angle cylinders allow you to operate each wing independently or lock the wings together for efficient straight blade operation and clean back dragging.

TRIP-EDGE PROTECTION

The trip-edge design helps protect you and your equipment when encountering hidden obstacles. Since only the bottom edge trips, the blade stays upright and plowed snow remains in front of the blade.

UTV-SPECIFIC HAND-HELD CONTROL

The unique hand-held control allows the blade to be raised, lowered, angled or retracted with the push of a button. Joystick control also available for easy blade control when wearing gloves.

EASY ON/OFF

With the receiver brackets installed on your utility vehicle, either drive in or manually push the plow into the receivers. Release the hitch pin handle, plug in the electrical and activate FLOAT on the control. Push up on the lift frame to allow hitch pins to fully engage the hitch pin holes. Verify the lock pin is engaged in the forward hole in the lock pin bracket.

ACCESSORIES AVAILABLE

- Shoe Kit
- Deflector Kit
- Blade Wing Kit



SPECIFICATIONS

Model	Blade Width	Blade Height	Blade Gauge	Trip Springs	Ribs	Lift Cylinder	Angling Rams	Plowing Width*	Approximate Weight**	Cutting Edge
TRAILBLAZER™ UTV V-PLOW	6' (1.83 m)	29½" (74.29 cm) at end 25¾" (65.40 cm) at hinge	14 (1.90 mm)	2	6	1" x 6" (2.54 cm x 15.24 cm)	1" x 8¾" (2.54 cm x 22.23 cm)	5' 0" (1.52 m) full angle 4' 7" (1.39 m) scoop 5' 0" (1.52 m) full V	354 lb (160 kg)	1¼" x 5" (0.64 cm x 12.70 cm)

* For UTVs with a wider wheelbase, width can be adjusted to: 5' 6" (1.68 m) full angle | 5' 1" (1.55 m) scoop | 5' 6" (1.68 m) full V
** Plus vehicle mount



Fisher Engineering | 50 Gordon Drive | Rockland, Maine 04841

fisherplows.com |



Fisher Engineering reserves the right under its product improvement policy to change construction or design details and furnish equipment when so altered without reference to illustrations or specifications used. Fisher Engineering or the vehicle manufacturer may require or recommend optional equipment for snow removal. Do not exceed vehicle ratings with a snowplow. This product is manufactured under the following patents 6,253,470; 7,400,058; 7,737,576; other patents pending. Fisher Engineering offers a limited warranty on all snowplows and accessories. See separately printed page for this important information. The following are registered (®) or unregistered (™) trademarks of Douglas Dynamics, LLC: FISHER®, Fish-Stik®, TRAILBLAZER™.