



NO SHEAR PINS HYDRAULIC RELIEF WINGS ATTACHMENT SYSTEM RECEIVER & FIFTH-WHEEL RAILS

STANDARD FEATURES

Quick Hitch System allows the operator to quickly and easily attach and detach the plow.

UHMW Cutting Edge and Curb Guards for superior scraping on any surface. Improves blade life and provides added protection.

Dual, Rear-Facing LED Lights increase visibility when operating in reverse.

Hydraulics and Linkage Inside the Blade allow operator to back closer to structures when backdragging.

Quick and Easy Control Panel Access with flexible draw latch for access to hydraulics.

Reduce Installation Time and Labor with no undercarriage to install.

2-Point Attachment System is designed for ¾ and 1-ton trucks equipped with a fifth-wheel rail system and a receiver hitch. Installation of a standard fifth-wheel rail kit, available at most truck equipment retailers, is required. With both points of attachment-fifth-wheel rail and receiver hitch-engaged, the DRAG PRO® 180Z offers advanced stability, rigidity and reliability for performance.

OPTIONAL ACCESSORIES



· Worklight Kit

• Taillight Kit











FORWARD





MODELS & SPECIFICATIONS

SPECS	MODEL	
	8'-16' Hydraulic Folding Wing	
Blade Width (Folded)	100" (254 cm)	SCAN FOR FULL
Blade Width (Fully Extended)	192" (488 cm)	SPECIFICATIONS
Moldboard Height	24" (61 cm)	
Plow Weight*	1,450 lb w/ hitch system (658 kg)	
Attachment System	Fifth-Wheel Rails and Receiver Hitch (2-Point Attachment)	一
Vehicle Application	4WD, ¾- and 1-ton trucks	